



CHEMICAL ASSOCIATES
1270 South Cleveland-Massillon Road
Building B
Copley, OH 44321-1683

MATERIAL SAFETY DATA SHEET

EMERGENCY PHONE: 800-347-2891

CHEMTREC: 800-424-9300

MSDS REFERENCE: CA1331FG, CA1331FK

SECTION I - IDENTIFICATION

PRODUCT: CA1331FG HIGH OLEIC ACID FOODGRADE
CA1331FK HIGH OLEIC ACID FOODGRADE KOSHER.
SYNONYMS: 9 - OCTADECENOIC ACID
CHEMICAL: UNSATURATED ALIPHATIC CARBOXYLIC ACID
CAS NO: 112-80-1
SARA HAZARD: NONE NOTED (SECTION 311/312)
TITLE III SECTION 313 NOT LISTED

SECTION II - INGREDIENTS AND HAZARD CLASSIFICATION

COMPOSITION	TYPICAL %	PEL/TLV	HAZARD
OLEIC ACID (112-80-1)	91	NONE/NONE	NONE NOTED
LINOLEIC ACID (60-33-3)	6	NONE/NONE	NONE NOTED
PALMITIC ACID (57-10-3)	1	NONE/NONE	NONE NOTED
STEARIC ACID (57-11-4)	1	NONE/NONE	NONE NOTED
MISC. FATTY ACIDS *	1	NONE/NONE	NONE NOTED
(*) C14-C22 CARBOXYLIC ACIDS			

SECTION III - HEALTH INFORMATION

INHALATION: UNKNOWN

INGESTION: LD50:>21.5 ML/KG (MALE ALBINO RATS)

EYE CONTACT: OLEIC ACID PRODUCED MILD CONJUNCTIVITIS IN FIVE OF SIX RABBITS. NO OTHER IRRITATIVE SIGNS WERE OBSERVED AND ALL EXCEPT ONE RABBIT SHOWED NO IRRITATIVE SIGNS AT THE 72-HOUR READING

SKIN CONTACT: OLEIC ACID PRODUCED VERY SLIGHT ERYTHEMA IN SIX INTACT AND SIX ABRADED SITES ON ALBINO RABBITS AT THE 24-HOUR READING ONLY. NO EDEMA WAS OBSERVED AT EITHER READING. PRIMARY IRRITATION INDEX WAS CALCULATED TO BE 0.50. 15 MG OF OLEIC ACID INTERMITTENTLY APPLIED TO HUMAN SKIN OVER A 3-DAY PERIOD RESULTED IN MODERATE IRRITATION. 500 MG OF

OLEIC ACID APPLIED TO RABBIT SKIN IN AN OPEN DRAIZE TEST RESULTED IN MILD IRRITATION.

SECTION IV - OCCUPATIONAL EXPOSURE LIMITS

PEL: NO OSHA PEL
TLV: NO ACGIH TLV

SECTION V - EMERGENCY FIRST AID PROCEDURE

INGESTION: NO ADVERSE EFFECTS ARE EXPECTED FROM THE INGESTION OF SMALL AMOUNTS OF THIS MATERIAL. DO NOT INDUCE VOMITING. IF CONSCIOUS, HAVE VICTIM DRINK 8-16 OZ OF WATER. IF DISTRESS OCCURS, CALL A PHYSICIAN OR POISON CONTROL CENTER PROMPTLY.

INHALATION: ADVERSE EFFECTS ARE EXPECTED ONLY FROM HEATED VAPORS. REMOVE VICTIM TO FRESH AIR. IF VICTIM HAS STOPPED BREATHING GIVE ARTIFICIAL RESPIRATION, PREFERABLY BY MOUTH TO MOUTH. GET MEDICAL ATTENTION IMMEDIATELY.

EYE CONTACT: IMMEDIATELY FLUSH EYES WITH PLENTY OF COOL WATER FOR AT LEAST 15 MINUTES. DO NOT LET VICTIM RUB EYES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

SKIN CONTACT: WASH AFFECTED AREA WITH SOAP AND WATER. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS. WASH CONTAMINATED CLOTHING BEFORE REUSE.

SECTION VI - PHYSICAL DATA

BOILING POINT: 545 DEG F (285 DEG C) AT 100 MM HG PRESSURE (APPROX.)

MELTING POINT: 14 DEG C (APPROX.)

VAPOR PRESSURE: 10 MM HG PRESSURE AT 224 DEG C

SPECIFIC GRAVITY: 0.89 AT 25/20 DEG C

SOLUBILITY IN WATER: INSOLUBLE

APPEARANCE AND COLOR: LIGHT COLOR WITH A FATTY ACID ODOR

SECTION VII - FIRE AND EXPLOSION HAZARDS

FLASH POINT AND METHOD USED: 364-372 DEG F CLOSED CUP

AUTO-IGNITION TEMPERATURE: 685 DEG. F (363 DEG C)

FLAMMABLE LIMITS IN AIR, % BY VOL. LOWER: NOT ESTABLISHED

FLAMMABLE LIMITS IN AIR, % BY VOL. UPPER: NOT ESTABLISHED

NFPA RATING: HEALTH: (0) FIRE: (1) REACTIVITY: (0) FOR OLEIC ACID

HMIS RATING: HEALTH: (1) FIRE: (1) REACTIVITY: (0)

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS:

(INDIVIDUALS SHOULD PERFORM ONLY THOSE FIRE PROCEDURES FOR WHICH THEY HAVE BEEN TRAINED.) WATER OR FOAM MAY CAUSE FROTHING WHEN APPLIED TO FLAMMABLE LIQUIDS HAVING FLASH POINTS ABOVE 212 DEG F (100 DEG C). THE REMARK IS INCLUDED ONLY AS A PRECAUTION AND DOES NOT MEAN THAT WATER OR FOAM SHOULD NOT OR COULD NOT BE USED IN FIGHTING FIRES IN SUCH LIQUIDS. THE FROTHING MAY BE QUITE VIOLENT AND COULD ENDANGER THE LIFE OF THE FIREFIGHTER PARTICULARLY WHEN SOLID STREAMS ARE DIRECTED INTO THE HOT BURNING LIQUID. ON THE OTHER HAND, WATER SPRAY CAREFULLY APPLIED HAS FREQUENTLY BEEN USED WITH SUCCESS IN EXTINGUISHING SUCH FIRES BY CAUSING

THE FROTHING TO OCCUR ONLY ON THE SURFACE AND THIS FOAMING ACTION BLANKETS AND EXTINGUISHES THE FIRE. (NFPA 325M-1984)

UNUSUAL FIRE AND EXPLOSION HAZARDS:

FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS IN THE POSITIVE-PRESSURE MODE WITH A FULL FACEPIECE WHEN THERE IS A POSSIBILITY OF EXPOSURE TO SMOKE, FUMES OR HAZARDOUS DECOMPOSITION PRODUCTS.

SECTION VIII - REACTIVITY

STABILITY:	GENERALLY STABLE
HAZARDOUS POLYMERIZATION:	NONE LIKELY
CONDITIONS AND MATERIALS TO AVOID:	AVOID CONTACT WITH STRONG OXIDIZING AGENTS AND STRONG ALKALIES.
HAZARDOUS DECOMPOSITION PRODUCTS:	DECOMPOSITION MAY PRODUCE CARBON MONOXIDE AND CARBON DIOXIDE.

SECTION IX - EMPLOYEE PROTECTION

CONTROL MEASURES:

HANDLE IN THE PRESENCE OF ADEQUATE VENTILATION.

RESPIRATORY PROTECTION:

RECOMMENDED EXPOSURE LIMITS (I.E., OSHA-PEL AND ACGIH-TLV) HAVE NOT BEEN ESTABLISHED FOR THIS MATERIAL. WHETHER THERE IS A NEED FOR RESPIRATORY PROTECTION UNDER YOUR CONDITIONS OF HANDLING OF THIS MATERIAL SHOULD BE EVALUATED BY A QUALIFIED HEALTH SPECIALIST.

PROTECTIVE CLOTHING:

WEAR GLOVES AND PROTECTIVE CLOTHING WHICH ARE IMPERVIOUS TO THE PRODUCT FOR THE DURATION OF ANTICIPATED EXPOSURE IF THERE IS POTENTIAL FOR PROLONGED OR REPEATED SKIN CONTACT.

EYE PROTECTION:

WEAR SAFETY GLASSES MEETING THE SPECIFICATIONS OF ANSI STANDARD Z87.1 WHERE NO CONTACT WITH THE EYE IS ANTICIPATED. CHEMICAL SAFETY GOGGLES MEETING THE SPECIFICATIONS OF ANSI STANDARD Z87.1 SHOULD BE WORN WHENEVER THERE IS THE POSSIBILITY OF SPLASHING OR OTHER CONTACT WITH THE EYES.

SECTION X - ENVIRONMENTAL PROTECTION

ENVIRONMENTAL PRECAUTIONS:

AVOID UNCONTROLLED RELEASES OF THIS MATERIAL. WHERE SPILLS ARE POSSIBLE, A COMPREHENSIVE SPILL RESPONSE PLAN SHOULD BE DEVELOPED AND IMPLEMENTED.

SPILL OR LEAK PRECAUTIONS:

WEAR APPROPRIATE RESPIRATORY PROTECTION AND PROTECTIVE CLOTHING AS DESCRIBED IN SECTION IX. CONTAIN SPILLED MATERIAL. TRANSFER TO SECURE CONTAINERS. WHERE NECESSARY, COLLECT USING ABSORBENT MEDIA. IN THE EVENT OF AN UNCONTROLLED RELEASE OF THIS MATERIAL, THE USER SHOULD DETERMINE IF THE RELEASE IS REPORTABLE UNDER APPLICABLE LAWS AND REGULATIONS.

WASTE DISPOSAL:

ALL RECOVERED MATERIAL SHOULD BE PACKAGED, LABELED, TRANSPORTED, AND DISPOSED OR RECLAIMED IN CONFORMANCE WITH APPLICABLE LAWS AND REGULATIONS AND IN CONFORMANCE WITH GOOD ENGINEERING PRACTICES. AVOID LANDFILLING OF LIQUIDS. RECLAIM WHERE POSSIBLE.

SECTION XI - REGULATORY CONTROLS

DEPARTMENT OF TRANSPORTATION:

DOT CLASSIFICATION: NOT REGULATED
DOT PROPER SHIPPING NAME:
OTHER DOT INFORMATION:

OTHER REGULATORY REQUIREMENTS:

USA TSCA COMPLIANT
CANADIAN DSL COMPLIANT
CANADIAN WHMIS, NOT CONTROLLED
EU EINCS COMPLIANT
AUSTRALIA AICS COMPLIANT
JAPAN ENCS COMPLIANT
CHINA IECS COMPLIANT
KOREA ECL COMPLIANT
PHILIPPINES PICCS COMPLIANT

CERCLA HAZARDOUS MATERIALS:

NONE NOTED

CALIFORNIA PROPOSITION 65 COMPONENTS

NONE

SECTION XII - PRECAUTIONS: HANDLING, STORAGE AND USAGE

NO SPECIAL PRECAUTIONS NECESSARY. AVOID CONTAINER DAMAGE WHILE HANDLING AND STORING.

The information presented herein is believed to be factual as it has been derived from the works and opinions of persons believed to be qualified experts; however, nothing contained in this information is to be taken as a warranty or representation for which Chemical Associates bears responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.

**CHEMICAL ASSOCIATES
1270B SOUTH CLEVELAND-MASSILLON ROAD
COPLEY, OHIO 44321-1683**

**DATE: 10/17/09
SUPERSEDES: 10/16/06**