



CHEMICAL ASSOCIATES
1270 South Cleveland-Massillon Road
Building B
Copley, OH 44321-1683

MATERIAL SAFETY DATA SHEET

EMERGENCY PHONE: 800-347-2891
MSDS REFERENCE: CA1405

CHEMTREC: 800-424-9300

SECTION I - IDENTIFICATION

WARNING: **MAY CAUSE SKIN AND EYE IRRITATION!**
DO NOT GET IN EYES, ON SKIN, OR ON CLOTHING. AVOID BREATHING VAPOR. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

PRODUCT: CA1405 COCONUT FATTY ACID

SYNONYMS:

CHEMICAL: ALIPHATIC CARBOXYLIC ACIDS

CAS NO: 67701-05-7

SARA HAZARD: NONE NOTED (SECTION 311/312)
TITLE III SECTION 313 NOT LISTED

SECTION II - INGREDIENTS AND HAZARD CLASSIFICATION

COMPOSITION	TYPICAL%	PEL/TLV	HAZARD
LAURIC ACID (143-07-7)	50	NONE/NONE	IRRITANT
MYRISTIC ACID (544-63-8)	18	NONE/NONE	NONE NOTED
PALMITIC ACID (57-10-3)	8	NONE/NONE	NONE NOTED
OCTANOIC ACID (CAPRYLIC) (124-07-2)	7	NONE/NONE	CORROSIVE
STEARIC ACID (57-11-4)	6	NONE/NONE	NONE NOTED
DECANOIC ACID (CAPRIC) (334-48-5)	6	NONE/NONE	CORROSIVE
OLEIC ACID (112-80-1)	4	NONE/NONE	NONE NOTED
HEXANOIC ACID (CAPROIC) (142-62-1)	1	NONE/NONE	CORROSIVE

SECTION III - HEALTH INFORMATION

INGESTION: LD50:>22 G/KG (ALBINO RATS) INCIDENTAL INGESTION MAY PRODUCE MILD GASTROINTESTINAL UPSET.

INHALATION: NO HARMFUL EFFECTS EXPECTED AT AMBIENT TEMPERATURES. VAPORS FROM HOT MATERIAL MAY PRODUCE RESPIRATORY IRRITATION.

EYE CONTACT: EXPECTED TO CAUSE MILD BUT TRANSIENT IRRITATION.

SKIN CONTACT: REPEATED OR PROLONGED SKIN CONTACT WILL PRODUCE IRRITATION.

SECTION IV - OCCUPATIONAL EXPOSURE LIMITS

PEL: NO OSHA PEL
TLV: NO ACGIH TLV

SECTION V - EMERGENCY FIRST AID PROCEDURE

INGESTION: DO NOT INDUCE VOMITING UNLESS OTHERWISE INSTRUCTED TO DO SO. CALL A PHYSICIAN OR POISON CONTROL CENTER .

INHALATION: IF RESPIRATORY DISTRESS IS EXPERIENCED, IMMEDIATELY REMOVE VICTIM TO FRESH AIR. IF VICTIM HAS STOPPED BREATHING GIVE ARTIFICIAL RESPIRATION, PREFERABLY BY MOUTH TO MOUTH. GET MEDICAL ATTENTION IMMEDIATELY.

EYE CONTACT: IMMEDIATELY FLUSH EYES WITH PLENTY OF COOL WATER FOR AT LEAST 15 MINUTES. DO NOT LET VICTIM RUB EYES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS AFTER FLUSHING.

SKIN CONTACT: PRACTICE GOOD INDUSTRIAL HYGIENE. WASH EXPOSED SKIN WITH PLENTY OF SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE REUSE.

SECTION VI - PHYSICAL DATA

BOILING POINT: >500 DEG F (260 DEG C) AT 760 MM HG PRESSURE (APPROX.)
MELTING POINT: 22-26 DEG C
VAPOR PRESSURE: 100 MM HG PRESSURE AT 445 DEG F (APPROX.)
SPECIFIC GRAVITY: 0.89 AT 75/25 DEG C
SOLUBILITY IN WATER: INSOLUBLE
APPEARANCE AND COLOR: LIGHT YELLOW, SEMI-SOLID. FATTY ACID ODOR.

SECTION VII - FIRE AND EXPLOSION HAZARDS

FLASH POINT AND METHOD USED: 315 DEG F (157 DEG C) COC
FLAMMABLE LIMITS IN AIR, % BY VOL. LOWER: NOT ESTABLISHED
FLAMMABLE LIMITS IN AIR, % BY VOL. UPPER: NOT ESTABLISHED
NFPA RATING: **NO NFPA RATING**
HMIS RATING: HEALTH: (1) FIRE: (1) **REACTIVITY: (0)**

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS:

INDIVIDUALS SHOULD PERFORM ONLY THOSE FIRE FIGHTING PROCEDURES FOR WHICH THEY HAVE BEEN TRAINED. WATER OR FOAM MAY CAUSE FROTHING WHEN APPLIED TO FLAMMABLE LIQUIDS HAVING FLASH POINTS ABOVE 212 DEG F (100 DEG C). THE REMARK IS INCLUDED ONLY AS A PRECAUTION AND DOES NOT MEAN THAT WATER OR FOAM SHOULD NOT OR COULD NOT BE USED IN FIGHTING FIRES IN SUCH LIQUIDS. THE FROTHING MAY BE QUITE VIOLENT AND COULD ENDANGER THE LIFE OF THE FIREFIGHTER PARTICULARLY WHEN SOLID STREAMS ARE DIRECTED INTO THE HOT BURNING LIQUID. ON THE OTHER HAND, WATER SPRAY CAREFULLY APPLIED HAS FREQUENTLY BEEN USED WITH SUCCESS IN

EXTINGUISHING SUCH FIRES BY CAUSING THE FROTHING TO OCCUR ONLY ON THE SURFACE AND THIS FOAMING ACTION BLANKETS AND EXTINGUISHES THE FIRE. (NFPA 325M-1984)

UNUSUAL FIRE AND EXPLOSION HAZARDS:

FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS IN THE POSITIVE-PRESSURE MODE WITH A FULL FACEPIECE WHEN THERE IS A POSSIBILITY OF EXPOSURE TO SMOKE, FUMES OR HAZARDOUS DECOMPOSITION PRODUCTS.

SECTION VIII - REACTIVITY

STABILITY:	GENERALLY STABLE
HAZARDOUS POLYMERIZATION:	NONE LIKELY
CONDITIONS AND MATERIALS TO AVOID:	AVOID CONTACT WITH STRONG OXIDIZING AGENTS AND STRONG ALKALIES.
HAZARDOUS DECOMPOSITION PRODUCTS:	DECOMPOSITION MAY PRODUCE CARBON MONOXIDE AND CARBON DIOXIDE.

SECTION IX - EMPLOYEE PROTECTION

CONTROL MEASURES:

HANDLE IN THE PRESENCE OF ADEQUATE VENTILATION.

RESPIRATORY PROTECTION:

RECOMMENDED EXPOSURE LIMITS (I.E., OSHA-PEL AND ACGIH-TLV) HAVE NOT BEEN ESTABLISHED FOR THIS MATERIAL. WHETHER THERE IS A NEED FOR RESPIRATORY PROTECTION UNDER YOUR CONDITIONS OF HANDLING OF THIS MATERIAL SHOULD BE EVALUATED BY A QUALIFIED HEALTH SPECIALIST.

PROTECTIVE CLOTHING:

WEAR GLOVES AND PROTECTIVE CLOTHING WHICH ARE IMPERVIOUS TO THE PRODUCT FOR THE DURATION OF ANTICIPATED EXPOSURE IF THERE IS POTENTIAL FOR PROLONGED OR REPEATED SKIN CONTACT.

EYE PROTECTION:

WEAR SAFETY GLASSES MEETING THE SPECIFICATIONS OF ANSI STANDARD Z87.1 WHERE NO CONTACT WITH THE EYE IS ANTICIPATED. CHEMICAL SAFETY GOGGLES MEETING THE SPECIFICATIONS OF ANSI STANDARD Z87.1 SHOULD BE WORN WHENEVER THERE IS THE POSSIBILITY OF SPLASHING OR OTHER CONTACT WITH THE EYES.

SECTION X - ENVIRONMENTAL PROTECTION

ENVIRONMENTAL PRECAUTIONS:

AVOID UNCONTROLLED RELEASES OF THIS MATERIAL. WHERE SPILLS ARE POSSIBLE, A COMPREHENSIVE SPILL RESPONSE PLAN SHOULD BE DEVELOPED AND IMPLEMENTED.

SPILL OR LEAK PRECAUTIONS:

WEAR APPROPRIATE RESPIRATORY PROTECTION AND PROTECTIVE CLOTHING AS DESCRIBED IN SECTION IX. CONTAIN SPILLED MATERIAL. TRANSFER TO SECURE CONTAINERS. WHERE NECESSARY, COLLECT USING ABSORBENT

MEDIA. IN THE EVENT OF AN UNCONTROLLED RELEASE OF THIS MATERIAL, THE USER SHOULD DETERMINE IF THE RELEASE IS REPORTABLE UNDER APPLICABLE LAWS AND REGULATIONS.

WASTE DISPOSAL:

ALL RECOVERED MATERIAL SHOULD BE PACKAGED, LABELED, TRANSPORTED, AND DISPOSED OR RECLAIMED IN CONFORMANCE WITH APPLICABLE LAWS AND REGULATIONS AND IN CONFORMANCE WITH GOOD ENGINEERING PRACTICES. AVOID LANDFILLING OF LIQUIDS. RECLAIM WHERE POSSIBLE.

SECTION XI - REGULATORY CONTROLS

DEPARTMENT OF TRANSPORTATION:

DOT CLASSIFICATION: NOT REGULATED
DOT PROPER SHIPPING NAME:
OTHER DOT INFORMATION:

OTHER REGULATORY REQUIREMENTS:

LISTED IN TSCA INVENTORY
LISTED ON CANADIAN DSL
LISTED IN EUROPEAN INVENTORY
LISTED IN AUSTRALIAN INVENTORY
LISTED IN JAPAN INVENTORY
LISTED IN KOREAN INVENTORY
LISTED IN PHILIPPINE INVENTORY
LISTED IN CHINA INVENTORY

CERCLA HAZARDOUS MATERIALS:

NONE NOTED

SECTION XII - PRECAUTIONS: HANDLING, STORAGE AND USAGE

KEEP IN CLOSED OR COVERED CONTAINERS AND DO NOT STORE NEAR HEAT OR OPEN FLAMES TO PRESERVE THE COLOR AND ODOR CHARACTERISTICS OF THIS PRODUCT.

The information presented herein is believed to be factual as it has been derived from the works and opinions of persons believed to be qualified experts; however, nothing contained in this information is to be taken as a warranty or representation for which Chemical Associates bears responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.

CHEMICAL ASSOCIATES
1270 SOUTH CLEVELAND-MASSILLON ROAD
COPLEY, OHIO 44321-1683

DATE: 01/20/12
SUPERSEDES: 09/16/10