

CA0430 Distilled Tall Oil

Safety Data Sheet



SECTION 1: Identification of the substance or mixture and the company or undertaking

1.1 Product identifier

Product type : Mixture
Trade name : CA0430 Distilled Tall Oil
Label name : CA0430 Distilled Tall Oil
Chemical name : Tall Oil Distillation Fractions
CAS number : 8002-26-4
EC number : 232-304-6

1.2 Recommended and restricted uses of the substance or mixture

Recommended uses : Intermediate in manufacture of soaps, amines, amides, esters, alkyd resins, for use in application areas such as emulsifiers for metalworking fluids, soaps in pine oil cleaners and synthetic detergents, and preparation of specialty corrosion inhibitors.
Restricted uses : None known.

1.3 Company identification

Company name : Chemical Associates – A Division of Univar USA Inc.
Company address : 1270 South Cleveland Massillon Road
: Copley, OH 44321-1683
Company telephone : 330-666-5200

1.4 Emergency telephone number

Company emergency telephone : 800-347-2891
CHEMTREC telephone : 800-424-9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (29CFR1910.1200 Appendix A) : Not hazardous.
GHS physical hazard : None.
GHS health hazard : None.
GHS environmental hazard : None.

2.2 Label warnings of the substance or mixture

Signal word : None.
Hazard statements : None.

CA0430 Distilled Tall Oil

Safety Data Sheet



Precautionary statements : P264 Wash hands thoroughly after handling.
Hazard symbol (pictogram) : None.

2.3 Hazards not otherwise classified

Other hazards : No additional information available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name	Common name	Percent	CAS number	Health hazard
Not applicable.				

3.2 Mixtures

Chemical name	Common name	Typical %	CAS number	Health hazard
Distilled Tall oil	Tall oil fatty acid	100	8002-26-4	None

SECTION 4: First-aid measures

4.1 Description of first-aid measures

Exposure route	First-aid measure
Inhalation	: Remove the victim into fresh air. Observe victim's breathing. If breathing is labored seek immediate medical attention.
Skin contact	: Wash immediately with soap and water. If irritation develops, seek medical attention. Launder contaminated clothing.
Eye contact	: Rinse immediately with plenty of water for 15 minutes. Remove contact lenses if present and easy to do. Do not use neutralizing agents. If irritation persists, seek immediate medical (ophthalmologist) attention.
Ingestion	: Rinse mouth with plenty of water. For ingestion of large quantities seek immediate medical attention. Do not induce vomiting. Contact poison control center.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms after inhalation	: May experience dizziness.
Symptoms after skin contact	: Mild irritation of the skin may occur.
Symptoms after eye contact	: Irritation of the eye tissue.
Symptoms after ingestion	: Mild tingling of the tongue and mouth.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment after inhalation	: If breathing is labored seek immediate medical attention.
Treatment after skin contact	: If skin irritation persists seek immediate medical attention.

CA0430 Distilled Tall Oil

Safety Data Sheet



Treatment after eye contact : If eye irritation persists seek immediate ophthalmologist attention.
Treatment after ingestion : If ingestion of a large quantity seek immediate poison control center.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable media : Carbon dioxide, dry chemical and water spray. Avoid using a direct stream of water
Unsuitable media : None known.

5.2 Specific hazards arising from the substance or mixture

Direct fire hazard : Not combustible.
: If porous materials such as rags or papers are soaked with mixture, spontaneous combustion may occur.
Indirect fire hazard : Exposure to temperature above the flash point (200 C).
Explosive hazard : Exposure to temperature above the flash point (200 C).
Reactivity : Reactivity with strong oxidizers or strong bases.
Combustion products : Carbon dioxide, carbon monoxide and oxides of sulfur.

5.3 Special protective equipment and precautions for fire-fighters

Protective equipment : Full protective clothing.
: Self contained breathing apparatus.
Precautions : No additional information available.
Emergency response guide : Not a hazardous material.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Mixture is not hazardous. If mixture is a mist, stay upwind.
Protective equipment : Wear rubber gloves, rubber boots, face shield and chemical hazard suit. If material is a mist wear dust mask or self contained breathing apparatus.
Emergency procedures : Mark the spill area with hazard tape or cones. Contain the spill area with suitable absorbent. Keep away from streams, rivers and lakes. If mixture is a mist, alert immediate neighborhood to close windows and doors. Contain and dissipate mist via spraying with water.

6.2 Environmental precautions

Precautions : Keep out of streams, rivers and lakes. Mixture is regulated as oil under the Clean Water Act. Abide by all laws per this regulation.

6.3 Methods and materials for containment and cleanup

CA0430 Distilled Tall Oil

Safety Data Sheet



Methods : Use chemical absorbent pigs or manually spread chemical absorbent onto spill area. After the mixture is absorbed, dispose in approved waste facility.

Materials : Approved materials include dry earth, sand, clay, chemical absorbent, vermiculite and carbon.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Handling temperature : About 10 C above the melt point (8 C).

Handling equipment : Rubber hoses or stainless steel (grade 304) lines. Stainless steel (grade 304) for pumps.

7.2 Conditions for safe storage, including any incompatibilities

Storage area : Store in dry area. Store at room temperature. Store in dyke area to contain any spills. Protect from heat.

Packaging materials : Polyethylene, stainless steel (grade 304), rubber lined or epoxy lined tanks or drums. Graphite or rubber gaskets.

Incompatibilities : Strong oxidizers and strong bases.

SECTION 8: Exposure controls/personal protection

8.1 Exposure controls

OSHA PEL : TWA 5 mg/m3 respirable.

ACGIH TLV : TWA 5 mg/m3 respirable; STEL 10mg/m3 respirable.

NIOSH REL : TWA 10 mg/m3 respirable.

8.2 Appropriate engineering controls

Engineering controls : If mist exists, install ventilation equipped with carbon canisters. Ventilation should be 10 air exchanges per hour. Local exhaust ventilation is recommended.

8.3 Personal protection equipment

Personal protective equipment : Rubber gloves and safety glasses. Dust mask if mist exists.

Personal protective equipment pictograms :



SECTION 9: Physical and chemical properties

CA0430 Distilled Tall Oil

Safety Data Sheet



9.1 Physical and chemical properties

Appearance	: Yellow liquid.
Odor	: Mild fatty acid odor.
Odor threshold	: No data available.
pH	: No data available. Mixture is not readily soluble in water.
Melting point	: No data available
Boiling point	: No data available
Flash point	: 199 C, Setaflash Closed Cup
Evaporation rate	: Approximately 0 (n-butyl acetate = 1)
Flammability	: Not flammable.
Lower flammability limit	: No data available.
Upper flammability limit	: No data available.
Vapor pressure	: < 0.001 mm Hg at 20 C.
Vapor density	: No data available.
Relative density	: 0.94 at 25/25 (water = 1.0).
Solubility	: Complete in ethanol and acetone. : In water 9 mg/l at 20 C.
Partition coefficient for n-octanol/water	: Log Kow = 4.9 – 7.7 at 30 C.
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available.
Viscosity	: No data available

9.2 Other information

Other information : No additional information available.

SECTION 10: Stability and reactivity

Reactivity	: May react violently with oxidizers.
Chemical stability	: Stable under storage conditions.
Possibility of hazardous reactions	: Hazardous polymerization does not occur.
Conditions to avoid	: This product mixture may self combust after sorption into porous materials such as cloth rags, paper, insulation or organic clay. : Pressure, shock, static discharge or vibration does NOT result in a hazardous condition.
Incompatible materials	: Oxidizers.
Hazardous decomposition products	: Carbon dioxide, carbon monoxide and oxides of sulfur.

SECTION 11: Toxicological information

11.1 Information on the likely routes of exposure

Inhalation exposure : From mist or spray.

CA0430 Distilled Tall Oil

Safety Data Sheet



Skin exposure : From mist or spray. From splashing.
Ingestion exposure : Not a likely route of exposure.
Eye contact : From mist or spray. From splashing.

11.2 Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Labored breathing and irritation of the lungs may occur.
Skin contact : Mild skin irritation may occur.
Ingestion : Mild irritation of the mouth, tongue, esophagus and stomach may occur.
Eye contact : Mild eye irritation may occur.

11.3 Delayed and immediate effects and also chronic effects from short and long term exposure

Inhalation : Chronic effects are not known.
Skin contact : Chronic effects are not known.
Ingestion : Chronic effects are not known.
Eye contact : Chronic effects are not known.

11.4 Numerical measures of toxicity

Oral LD50 : Rat > 5000mg/kg.
Skin LD50 : Not found to be a skin irritant in rabbits.
Ingestion LD50 : Not found to be a eye irritant in rabbits.
Inhalation LD50 : No data available.
Skin primary irritation : No data available.
Eye primary irritation : No data available

11.5 Carcinogenicity

National Toxicology Program : Not listed.
International Agency for
Research on Cancer : Not listed.
OSHA : Not listed.
NIOSH : Not listed.

11.6 Other toxicological information

Reproductive toxicity : Not classified.
Germ cell mutagenicity : Not classified.
Respiratory or skin sensitization : No data available.
Specific target organ toxicity,
single exposure : No data available.
Specific target organ toxicity,
repeated exposure : No data available.
Aspiration hazard : No data available.

CA0430 Distilled Tall Oil

Safety Data Sheet



SECTION 12: Ecological information

12.1.1 Ecotoxicity aquatic

Fish LL50 : 96-hr LL₅₀ >1000 mg/l loading rate WAF; NOEL 1000 mg/l loading rate WAF
Daphnia EC50 : 48-hr EL₅₀ >1000 mg/l loading rate WAF; NOEL 1000 mg/l loading rate WAF
Algae EL50 : 72-hr EL₅₀ > for AUC = 1000 mg/l loading rate WAF; NOEL 1000 mg/l loading rate WAF

12.1.2 Ecotoxicity terrestrial

Ecotoxicity terrestrial : No data available.

12.2 Persistence and degradability

Water : 73% 28 days STURM OECD 301B.
: Readily biodegradable.
Soil : Koc = 340,000 (oleic acid).
: Koc = 163,000 (linoleic acid).
: 0.20 - 0.66 days half life (oleic acid).
: Immobile.
Air : 5.1 hour half life (oleic acid).
: 3.0 hour half life (linoleic acid).

12.3 Bio-accumulative potential

Log Kow : 4.9 - 7.7 at 30 C.
: The mixture has a potential to bioaccumulate

12.4 Mobility in soil

Surface tension : Air 64 mN/m at 22 C.
Soil mobility : Koc = 340,000 (oleic acid).
: Koc = 163,000 (linoleic acid).
: Immobile.

12.5 Results of PBT and vPvB assessment

PBT and vPvB assessment : No data available.

12.6 Other adverse effects

Air : Not dangerous to the ozone layer.
Water : Mild pollutant to surface of water.
: Bio-accumulative.

CA0430 Distilled Tall Oil

Safety Data Sheet



SECTION 13: Disposal considerations

13.1 Description of waste residues

Storage tank residues : Liquid residue from tank cleaning.
Empty package residues : Liquid residue remaining in emptied package container.
Transport trailer residues : Liquid residue from transport trailer cleaning.
Absorbent material : Solid absorbent containing mixture from a spill.

13.2 Safe handling of waste residues

Storage tank residues : Refer to section 7 for safe handling.
Empty package residues : Refer to section 7 for safe handling.
Transport trailer residues : Refer to section 7 for safe handling.
Absorbent material : Refer to section 7 for safe handling.

13.3 Methods of disposal

Storage tank residues : Dispose via an approved incineration facility.
: Dispose via an approved land fill facility.
Empty package residues : Dispose only in accordance with local, state and federal regulations.
: Remove package to an approved package cleaning and recycling facility.
Transport trailer residues : Dispose only in accordance with local, state and federal regulations.
: Clean transport trailer at an approved cleaning facility.
: Disposal of cleaning residues must be in accordance with local, state and federal regulations.
Absorbent material : Dispose via an approved incineration facility.
: Dispose via an approved land fill facility.
: Dispose only in accordance with local, state and federal regulations.

13.4 Hazardous waste classification (RCRA)

Classification	Regulation	Listed	Hazardous waste number
Ignitability	40CFR261.21	No	
Corrosivity	40CFR261.22	No	
Reactivity	40CFR261.23	No	
Toxicity	40CFR261.24	No	

SECTION 14: Transport information

14.1 UN number

UN number : Not regulated.

14.2 UN proper shipping name

CA0430 Distilled Tall Oil

Safety Data Sheet



Proper shipping name : None.

14.3 Transport hazard class

Hazard class : None.
Hazard label : None.
Hazard pictogram : None.

14.4 Packing group

Packing group : None.

14.5 Environmental hazards

Marine pollutant : Not listed, per 49CFR172.101 Appendix B.

14.6 Transport in bulk

US DOT : Not regulated.
IMDG : Not regulated.
IATA : Not regulated.
MARPOL 73/78 : Not regulated.
IBC code : Not regulated.

14.7 Special precautions for user

Special precautions : No additional information available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the substance or mixture

15.1.1 US regulations

SARA 302 (40CFR355) : Not listed.
SARA 311/312 (40CFR370.66) : Not listed.
SARA 313 (40CFR372.65) : Not listed.
CERCLA (40CFR302.4) : Not listed.
California proposition 65 : Not listed.
German WGK class : 1 (low hazard to waters).

15.1.2 Chemical inventories

TSCA USA : Listed.
AICS Australia : Listed.
DSL Canada : Listed.

CA0430 Distilled Tall Oil

Safety Data Sheet



EC Europe : Listed.
ECL Korea : Listed.
IECSC China : Listed.
ENCS Japan : Listed.
NzloC New Zealand : Unknown.
PICCS Philippines : Listed.
SWISS Switzerland : Unknown.

15.2 Chemical safety assessment

Safety assessment : No additional information available.

SECTION 16: Other information

16.1 Hazard ratings

	Health	Flammability	Physical hazards	Instability
HMIS (USA)	1	1	0	
NFPA (USA)	1	1		0

16.2 Safety Data Sheet information

Revision date (MM/DD/YY) : 07/31/13
Supersede date (MM/DD/YY) : 09/20/10

16.3 Notice to reader

The information presented herein is believed to be factual as it has been derived from the works and opinions of persons believed to be qualified experts; however, nothing contained in this information is to be taken as a warranty or representation for which Chemical Associates – A Division of Univar USA Inc. bears responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.